

PERFORMANCE
RELIABILITY
AND
VALUE

HDMI to Composite with Audio Converter

Convert HDMI signal into Composite video and audio



The KanexPro HDMI to Composite with Audio Converter is a classic retro fit device, engineered to transform HDMI signals into analog composite video with R/L audio. Connect your HD sources such as DVD and Blu-ray players or, PC and game consoles to an analog A/V monitor or a projector. The converter includes a front panel switch that supports PAL/NTSC formats for different regions and works flawlessly with all HDMI devices that are not HDCP encrypted.

Features

- Convert HDMI signal into Composite video and audio
- Supports HDMI input resolutions up to 1080p(1920x1080@60Hz)
- Analog composite video output up to NTSC 480i or PAL 576i
- Decodes uncompressed analog audio signal from HDMI
- Rack or under-desk mountable
- 5VDC external power supply included

Specifications

Input: HDMI x1
Output: RCA x1
Video Amplifier Bandwidth: 1.65Gbps
Vertical Frequency Range: 50/60Hz
Resolutions: HDMI input: 480i/576i/480p/576p/720p/1080i/1080P
 RCA output: NTSC/480i or 576p/PAL
Audio Output: 2 Channel LPCM
Power Supply: 5V DC@2A, 5W
Operating Temperature: 0°C to +70°C

Operating Humidity: 10% to 85 % RH (no condensation)
Storage Temperature: -10°C to +80°C
Storage Humidity: 5% to 90 % RH (no condensation)
Regulatory Approvals Converter: FCC, CE, UL
Regulatory Approvals Power Supply: FCC, CE, UL
Dimensions: 4"x3.9"x1" (102x100x25mm)
Total Weight: 1.4lbs (615g)
Warranty: 1 Year parts and labor

About KanexPro

KanexPro carries a broad selection of A/V connectivity products by leveraging the core strength in professional systems enabling you to broadcast, convert, extend, split, or multiply HD signal transmissions; simply and cost-effectively.

KanexPro

1405 Pioneer St.
Brea CA 92821

562-501-9380

info@kanexpro.com

www.kanexpro.com

Connection Diagram

Source

Display

